



Applications

For supervisory electrical equipment, station control circuits, outdoor, suitable installation in dry or wet cable trenches.

Cable Construction

Conductor	Concentric stranded annealed copper wires, Sizes: 0.5 mm ² up to 6 mm ²
Insulation	Polyvinyl chloride (PVC)
Color	2-4 cores : Black, White, Red and Green
	More than 4 cores : Black core with marking numbers
Filler	Non-hygroscopic material(optional)
Binding tape	Polyester (Mylar) tape (optional)
Sheath	Polyvinyl chloride (PVC), Black color (A Special FR-PVC flame retardant sheath can be supplied)

Technical Characteristics

Maximum conductor temperature 70°C
Circuit voltage not exceeding 600 volts
Test voltage 2000volts(JIS) / 3500 volts(IEC)

Cable Parameter

Cables to IEC 60502-1

No. of cores	Conductor			Thickness of insulation	Thickness of Sheath	Overall diameter	Maximum conductor resistance (at 20°C)	Minimum insulation resistance (at 70°C)	Cable weight
	Nominal cross sectional area	No.& dia. of wires	Diameter						
	mm ²	mm	mm	mm	mm	mm	Ohm/km	Ohm/km	kg/km
2	0.5	7/0.30	0.9	0.8	1.8	9.5	36	0.0162	100
2	0.75	7/0.37	1.11	0.8	1.8	10	24.5	0.0142	110
2	1	7/0.43	1.29	0.8	1.8	10.5	18.1	0.0128	120
2	1.5	7/0.52	1.56	0.8	1.8	11	12.1	0.0112	140
2	2.5	7/0.67	2.01	0.8	1.8	12	7.41	0.0093	180
2	4	7/0.85	2.55	1	1.8	14	4.61	0.0092	250
2	6	7/1.04	3.12	1	1.8	15.5	3.08	0.0078	310

3	0.5	7/0.30	0.9	0.8	1.8	10	36	0.0162	110
3	0.75	7/0.37	1.11	0.8	1.8	10.5	24.5	0.0142	130
3	1	7/0.43	1.29	0.8	1.8	11	18.1	0.0128	140
3	1.5	7/0.52	1.56	0.8	1.8	12	12.1	0.0112	170
3	2.5	7/0.67	2.01	0.8	1.8	13	7.41	0.0093	210
3	4	7/0.85	2.55	1	1.8	15	4.61	0.0092	310
3	6	7/1.04	3.12	1	1.8	16	3.08	0.0078	390
4	0.5	7/0.30	0.9	0.8	1.8	11	36	0.0162	130
4	0.75	7/0.37	1.11	0.8	1.8	11.5	24.5	0.0142	150
4	1	7/0.43	1.29	0.8	1.8	12	18.1	0.0128	170
4	1.5	7/0.52	1.56	0.8	1.8	12.5	12.1	0.0112	200
4	2.5	7/0.67	2.01	0.8	1.8	14	7.41	0.0093	260
4	4	7/0.85	2.55	1	1.8	16	4.61	0.0092	380
4	6	7/1.04	3.12	1	1.8	17.5	3.08	0.0078	490
5	0.5	7/0.30	0.9	0.8	1.8	12	36	0.0162	150
5	0.75	7/0.37	1.11	0.8	1.8	12.5	24.5	0.0142	180
5	1	7/0.43	1.29	0.8	1.8	13	18.1	0.0128	200
5	1.5	7/0.52	1.56	0.8	1.8	13.5	12.1	0.0112	240
5	2.5	7/0.67	2.01	0.8	1.8	15	7.41	0.0093	320
5	4	7/0.85	2.55	1	1.8	17.5	4.61	0.0092	470
5	6	7/1.04	3.12	1	1.8	19	3.08	0.0078	600
6	0.5	7/0.30	0.9	0.8	1.8	12.5	36	0.0162	160
6	0.75	7/0.37	1.11	0.8	1.8	13.5	24.5	0.0142	190
6	1	7/0.43	1.29	0.8	1.8	14	18.1	0.0128	220
6	1.5	7/0.52	1.56	0.8	1.8	14.5	12.1	0.0112	260
6	2.5	7/0.67	2.01	0.8	1.8	16	7.41	0.0093	340
6	4	7/0.85	2.55	1	1.8	19	4.61	0.0092	510
6	6	7/1.04	3.12	1	1.8	20.5	3.08	0.0078	660
7	0.5	7/0.30	0.9	0.8	1.8	12.5	36	0.0162	170
7	0.75	7/0.37	1.11	0.8	1.8	13.5	24.5	0.0142	200
7	1	7/0.43	1.29	0.8	1.8	14	18.1	0.0128	230
7	1.5	7/0.52	1.56	0.8	1.8	14.5	12.1	0.0112	270

7	2.5	7/0.67	2.01	0.8	1.8	16	7.41	0.0093	370
7	4	7/0.85	2.55	1	1.8	19	4.61	0.0092	540
7	6	7/1.04	3.12	1	1.8	20.5	3.08	0.0078	720
8	0.5	7/0.30	0.9	0.8	1.8	13.5	36	0.0162	190
8	0.75	7/0.37	1.11	0.8	1.8	14	24.5	0.0142	220
8	1	7/0.43	1.29	0.8	1.8	15	18.1	0.0128	250
8	1.5	7/0.52	1.56	0.8	1.8	15.5	12.1	0.0112	310
8	2.5	7/0.67	2.01	0.8	1.8	17	7.41	0.0093	410
8	4	7/0.85	2.55	1	1.8	20.5	4.61	0.0092	610
8	6	7/1.04	3.12	1	1.8	22.5	3.08	0.0078	810
9	0.5	7/0.30	0.9	0.8	1.8	14.5	36	0.0162	210
9	0.75	7/0.37	1.11	0.8	1.8	15	24.5	0.0142	250
9	1	7/0.43	1.29	0.8	1.8	16	18.1	0.0128	280
9	1.5	7/0.52	1.56	0.8	1.8	17	12.1	0.0112	340
9	2.5	7/0.67	2.01	0.8	1.8	18.5	7.41	0.0093	460
9	4	7/0.85	2.55	1	1.8	22	4.61	0.0092	690
9	6	7/1.04	3.12	1	1.8	24	3.08	0.0078	920
10	0.5	7/0.30	0.9	0.8	1.8	15.5	36	0.0162	230
10	0.75	7/0.37	1.11	0.8	1.8	16	24.5	0.0142	270
10	1	7/0.43	1.29	0.8	1.8	17	18.1	0.0128	310
10	1.5	7/0.52	1.56	0.8	1.8	18	12.1	0.0112	370
10	2.5	7/0.67	2.01	0.8	1.8	20	7.41	0.0093	510
10	4	7/0.85	2.55	1	1.8	24	4.61	0.0092	760
10	6	7/1.04	3.12	1	1.8	26	3.08	0.0078	1000
11	0.5	7/0.30	0.9	0.8	1.8	16	36	0.0162	250
11	0.75	7/0.37	1.11	0.8	1.8	16.5	24.5	0.0142	290
11	1	7/0.43	1.29	0.8	1.8	17.5	18.1	0.0128	340
11	1.5	7/0.52	1.56	0.8	1.8	18.5	12.1	0.0112	410
11	2.5	7/0.67	2.01	0.8	1.8	20.5	7.41	0.0093	560
11	4	7/0.85	2.55	1	1.8	24.5	4.61	0.0092	840
11	6	7/1.04	3.12	1	1.8	27	3.08	0.0078	1120
12	0.5	7/0.30	0.9	0.8	1.8	16	36	0.0162	250

12	0.75	7/0.37	1.11	0.8	1.8	16.5	24.5	0.0142	300
12	1	7/0.43	1.29	0.8	1.8	17.5	18.1	0.0128	350
12	1.5	7/0.52	1.56	0.8	1.8	18.5	12.1	0.0112	430
12	2.5	7/0.67	2.01	0.8	1.8	20.5	7.41	0.0093	580
12	4	7/0.85	2.55	1	1.8	24.5	4.61	0.0092	880
12	6	7/1.04	3.12	1	1.8	27	3.08	0.0078	1170
13	0.5	7/0.30	0.9	0.8	1.8	16.5	36	0.0162	280
13	0.75	7/0.37	1.11	0.8	1.8	17.5	24.5	0.0142	330
13	1	7/0.43	1.29	0.8	1.8	18.5	18.1	0.0128	380
13	1.5	7/0.52	1.56	0.8	1.8	19.5	12.1	0.0112	470
13	2.5	7/0.67	2.01	0.8	1.8	21.5	7.41	0.0093	640
13	4	7/0.85	2.55	1	1.8	26	4.61	0.0092	970
13	6	7/1.04	3.12	1	1.8	28.5	3.08	0.0078	1290
14	0.5	7/0.30	0.9	0.8	1.8	16.5	36	0.0162	280
14	0.75	7/0.37	1.11	0.8	1.8	17.5	24.5	0.0142	340
14	1	7/0.43	1.29	0.8	1.8	18.5	18.1	0.0128	390
14	1.5	7/0.52	1.56	0.8	1.8	19.5	12.1	0.0112	480
14	2.5	7/0.67	2.01	0.8	1.8	21.5	7.41	0.0093	660
14	4	7/0.85	2.55	1	1.8	26	4.61	0.0092	1000
14	6	7/1.04	3.12	1	1.8	28.5	3.08	0.0078	1340
15	0.5	7/0.30	0.9	0.8	1.8	17.5	36	0.0162	310
15	0.75	7/0.37	1.11	0.8	1.8	18.5	24.5	0.0142	370
15	1	7/0.43	1.29	0.8	1.8	19	18.1	0.0128	430
15	1.5	7/0.52	1.56	0.8	1.8	20.5	12.1	0.0112	530
15	2.5	7/0.67	2.01	0.8	1.8	22.5	7.41	0.0093	730
15	4	7/0.85	2.55	1	1.8	27	4.61	0.0092	1100
15	6	7/1.04	3.12	1	1.8	30	3.08	0.0078	1480
16	0.5	7/0.30	0.9	0.8	1.8	17.5	36	0.0162	320
16	0.75	7/0.37	1.11	0.8	1.8	18.5	24.5	0.0142	380
16	1	7/0.43	1.29	0.8	1.8	19	18.1	0.0128	440
16	1.5	7/0.52	1.56	0.8	1.8	20.5	12.1	0.0112	540
16	2.5	7/0.67	2.01	0.8	1.8	22.5	7.41	0.0093	750

16	4	7/0.85	2.55	1	1.8	27	4.61	0.0092	1140
16	6	7/1.04	3.12	1	1.8	30	3.08	0.0078	1530
17	0.5	7/0.30	0.9	0.8	1.8	18	36	0.0162	340
17	0.75	7/0.37	1.11	0.8	1.8	19	24.5	0.0142	410
17	1	7/0.43	1.29	0.8	1.8	20	18.1	0.0128	480
17	1.5	7/0.52	1.56	0.8	1.8	21.5	12.1	0.0112	590
17	2.5	7/0.67	2.01	0.8	1.8	23.5	7.41	0.0093	820
17	4	7/0.85	2.55	1	1.8	28.5	4.61	0.0092	1240
17	6	7/1.04	3.12	1	1.9	31.5	3.08	0.0078	1660
18	0.5	7/0.30	0.9	0.8	1.8	18	36	0.0162	350
18	0.75	7/0.37	1.11	0.8	1.8	19	24.5	0.0142	420
18	1	7/0.43	1.29	0.8	1.8	20	18.1	0.0128	490
18	1.5	7/0.52	1.56	0.8	1.8	21.5	12.1	0.0112	610
18	2.5	7/0.67	2.01	0.8	1.8	23.5	7.41	0.0093	840
18	4	7/0.85	2.55	1	1.8	28.5	4.61	0.0092	1280
18	6	7/1.04	3.12	1	1.8	31.5	3.08	0.0078	1720
19	0.5	7/0.30	0.9	0.8	1.8	18	36	0.0162	360
19	0.75	7/0.37	1.11	0.8	1.8	19	24.5	0.0142	430
19	1	7/0.43	1.29	0.8	1.8	20	18.1	0.0128	500
19	1.5	7/0.52	1.56	0.8	1.8	21.5	12.1	0.0112	620
19	2.5	7/0.67	2.01	0.8	1.8	23.5	7.41	0.0093	860
19	4	7/0.85	2.55	1	1.8	28.5	4.61	0.0092	1310
19	6	7/1.04	3.12	1	1.8	31.5	3.08	0.0078	1770
20	0.5	7/0.30	0.9	0.8	1.8	19	36	0.0162	380
20	0.75	7/0.37	1.11	0.8	1.8	20	24.5	0.0142	460
20	1	7/0.43	1.29	0.8	1.8	21	18.1	0.0128	540
20	1.5	7/0.52	1.56	0.8	1.8	22.5	12.1	0.0112	670
20	2.5	7/0.67	2.01	0.8	1.8	25	7.41	0.0093	930
20	4	7/0.85	2.55	1	1.8	30	4.61	0.0092	1420
20	6	7/1.04	3.12	1	1.9	33.5	3.08	0.0078	1920
21	0.5	7/0.30	0.9	0.8	1.8	19	36	0.0162	390
21	0.75	7/0.37	1.11	0.8	1.8	20	24.5	0.0142	470

21	1	7/0.43	1.29	0.8	1.8	21	18.1	0.0128	550
21	1.5	7/0.52	1.56	0.8	1.8	22.5	12.1	0.0112	680
21	2.5	7/0.67	2.01	0.8	1.8	25	7.41	0.0093	940
21	4	7/0.85	2.55	1	1.8	30	4.61	0.0092	1440
21	6	7/1.04	3.12	1	1.9	33.5	3.08	0.0078	1960
22	0.5	7/0.30	0.9	0.8	1.8	20	36	0.0162	420
22	0.75	7/0.37	1.11	0.8	1.8	21	24.5	0.0142	510
22	1	7/0.43	1.29	0.8	1.8	22	18.1	0.0128	590
22	1.5	7/0.52	1.56	0.8	1.8	23.5	12.1	0.0112	740
22	2.5	7/0.67	2.01	0.8	1.8	26	7.41	0.0093	1030
22	4	7/0.85	2.55	1	1.9	32	4.61	0.0092	1580
22	6	7/1.04	3.12	1	2	35.5	3.08	0.0078	2140
23	0.5	7/0.30	0.9	0.8	1.8	20	36	0.0162	430
23	0.75	7/0.37	1.11	0.8	1.8	21	24.5	0.0142	520
23	1	7/0.43	1.29	0.8	1.8	22	18.1	0.0128	600
23	1.5	7/0.52	1.56	0.8	1.8	23.5	12.1	0.0112	750
23	2.5	7/0.67	2.01	0.8	1.8	26	7.41	0.0093	1050
23	4	7/0.85	2.55	1	1.9	32	4.61	0.0092	1620
23	6	7/1.04	3.12	1	2	35.5	3.08	0.0078	2190
24	0.5	7/0.30	0.9	0.8	1.8	21	36	0.0162	440
24	0.75	7/0.37	1.11	0.8	1.8	22	24.5	0.0142	530
24	1	7/0.43	1.29	0.8	1.8	23	18.1	0.0128	620
24	1.5	7/0.52	1.56	0.8	1.8	25	12.1	0.0112	770
24	2.5	7/0.67	2.01	0.8	1.8	27.5	7.41	0.0093	1070
24	4	7/0.85	2.55	1	1.9	34	4.61	0.0092	1660
24	6	7/1.04	3.12	1	2	37.5	3.08	0.0078	2250
25	0.5	7/0.30	0.9	0.8	1.8	21.5	36	0.0162	460
25	0.75	7/0.37	1.11	0.8	1.8	22.5	24.5	0.0142	560
25	1	7/0.43	1.29	0.8	1.8	23.5	18.1	0.0128	660
25	1.5	7/0.52	1.56	0.8	1.8	25.5	12.1	0.0112	820
25	2.5	7/0.67	2.01	0.8	1.8	28	7.41	0.0093	1140
25	4	7/0.85	2.55	1	1.9	34.5	4.61	0.0092	1760

25	6	7/1.04	3.12	1	2	38.5	3.08	0.0078	2390
26	0.5	7/0.30	0.9	0.8	1.8	21.5	36	0.0162	470
26	0.75	7/0.37	1.11	0.8	1.8	22.5	24.5	0.0142	570
26	1	7/0.43	1.29	0.8	1.8	23.5	18.1	0.0128	670
26	1.5	7/0.52	1.56	0.8	1.8	25.5	12.1	0.0112	830
26	2.5	7/0.67	2.01	0.8	1.8	28	7.41	0.0093	1160
26	4	7/0.85	2.55	1	1.9	34.5	4.61	0.0092	1800
26	6	7/1.04	3.12	1	2	38.5	3.08	0.0078	2440
27	0.5	7/0.30	0.9	0.8	1.8	21.5	36	0.0162	480
27	0.75	7/0.37	1.11	0.8	1.8	22.5	24.5	0.0142	580
27	1	7/0.43	1.29	0.8	1.8	23.5	18.1	0.0128	680
27	1.5	7/0.52	1.56	0.8	1.8	25.5	12.1	0.0112	840
27	2.5	7/0.67	2.01	0.8	1.8	28	7.41	0.0093	1190
27	4	7/0.85	2.55	1	1.9	34.5	4.61	0.0092	1830
27	6	7/1.04	3.12	1	2	38.5	3.08	0.0078	2500
28	0.5	7/0.30	0.9	0.8	1.8	22	36	0.0162	500
28	0.75	7/0.37	1.11	0.8	1.8	23.5	24.5	0.0142	610
28	1	7/0.43	1.29	0.8	1.8	24.5	18.1	0.0128	720
28	1.5	7/0.52	1.56	0.8	1.8	26.5	12.1	0.0112	900
28	2.5	7/0.67	2.01	0.8	1.8	29	7.41	0.0093	1260
28	4	7/0.85	2.55	1	2	36	4.61	0.0092	1960
28	6	7/1.04	3.12	1	2.1	40	3.08	0.0078	2660
29	0.5	7/0.30	0.9	0.8	1.8	22	36	0.0162	510
29	0.75	7/0.37	1.11	0.8	1.8	23.5	24.5	0.0142	620
29	1	7/0.43	1.29	0.8	1.8	24.5	18.1	0.0128	730
29	1.5	7/0.52	1.56	0.8	1.8	26.5	12.1	0.0112	910
29	2.5	7/0.67	2.01	0.8	1.8	29	7.41	0.0093	1280
29	4	7/0.85	2.55	1	2	36	4.61	0.0092	2000
29	6	7/1.04	3.12	1	2.1	40	3.08	0.0078	2720
30	0.5	7/0.30	0.9	0.8	1.8	22	36	0.0162	520
30	0.75	7/0.37	1.11	0.8	1.8	23.5	24.5	0.0142	630
30	1	7/0.43	1.29	0.8	1.8	24.5	18.1	0.0128	740

30	1.5	7/0.52	1.56	0.8	1.8	26.5	12.1	0.0112	930
30	2.5	7/0.67	2.01	0.8	1.8	29	7.41	0.0093	1300
30	4	7/0.85	2.55	1	2	36	4.61	0.0092	2030
30	6	7/1.04	3.12	1	2.1	40	3.08	0.0078	2770

Cables to JIS C 3401

No. of cores	Conductor			Thickness of insulation	Thickness of Sheath	Overall diameter	Maximum conductor resistance (at 20°C)	Minimum insulation resistance (at 70°C)	Cable weight
	Nominal cross sectional area	No.& dia. of wires	Diameter						
	mm ²	mm	mm	mm	mm	mm	Ohm/km	Ohm/km	kg/km
2	1	7/0.43	1.29	0.72	1.35	11	19.5	0.05	86
2	1.5	7/0.52	1.56	0.72	1.35	11	13.3	0.05	103
2	2.5	7/0.67	2.01	0.72	1.35	12	7.98	0.05	132
2	4	7/0.85	2.55	0.72	1.35	13	4.95	0.05	174
2	6	7/1.04	3.12	0.9	1.35	15	3.3	0.05	241
3	1	7/0.43	1.29	0.72	1.35	11	19.5	0.05	103
3	1.5	7/0.52	1.56	0.72	1.35	12	13.3	0.05	126
3	2.5	7/0.67	2.01	0.72	1.35	13	7.98	0.05	166
3	4	7/0.85	2.55	0.72	1.35	14	4.95	0.05	225
3	6	7/1.04	3.12	0.9	1.35	16	3.3	0.05	315
4	1	7/0.43	1.29	0.72	1.35	12	19.5	0.05	124
4	1.5	7/0.52	1.56	0.72	1.35	13	13.3	0.05	153
4	2.5	7/0.67	2.01	0.72	1.35	14	7.98	0.05	205
4	4	7/0.85	2.55	0.72	1.35	15	4.95	0.05	281
4	6	7/1.04	3.12	0.9	1.35	17	3.3	0.05	398
5	1	7/0.43	1.29	0.72	1.35	13	19.5	0.05	145
5	1.5	7/0.52	1.56	0.72	1.35	14	13.3	0.05	182
5	2.5	7/0.67	2.01	0.72	1.35	15	7.98	0.05	246
5	4	7/0.85	2.55	0.72	1.35	16	4.95	0.05	338
5	6	7/1.04	3.12	0.9	1.35	19	3.3	0.05	484
6	1	7/0.43	1.29	0.72	1.35	14	19.5	0.05	168
6	1.5	7/0.52	1.56	0.72	1.35	14	13.3	0.05	211
6	2.5	7/0.67	2.01	0.72	1.35	16	7.98	0.05	288

6	4	7/0.85	2.55	0.72	1.35	17	4.95	0.05	399
6	6	7/1.04	3.12	0.9	1.35	20	3.3	0.05	573
7	1	7/0.43	1.29	0.72	1.35	14	19.5	0.05	181
7	1.5	7/0.52	1.56	0.72	1.35	14	13.3	0.05	230
7	2.5	7/0.67	2.01	0.72	1.35	16	7.98	0.05	316
7	4	7/0.85	2.55	0.72	1.35	17	4.95	0.05	442
7	6	7/1.04	3.12	0.9	1.35	20	3.3	0.05	637
8	1	7/0.43	1.29	0.72	1.35	14	19.5	0.05	205
8	1.5	7/0.52	1.56	0.72	1.35	15	13.3	0.05	260
8	2.5	7/0.67	2.01	0.72	1.35	17	7.98	0.05	359
8	4	7/0.85	2.55	0.72	1.35	19	4.95	0.05	503
8	6	7/1.04	3.12	0.9	1.35	22	3.3	0.05	727
9	1	7/0.43	1.29	0.72	1.35	15	19.5	0.05	228
9	1.5	7/0.52	1.56	0.72	1.35	16	13.3	0.05	290
9	2.5	7/0.67	2.01	0.72	1.35	18	7.98	0.05	403
9	4	7/0.85	2.55	0.72	1.35	20	4.95	0.05	566
9	6	7/1.04	3.12	0.9	1.35	23	3.3	0.05	819
10	1	7/0.43	1.29	0.72	1.35	16	19.5	0.05	256
10	1.5	7/0.52	1.56	0.72	1.35	17	13.3	0.05	326
10	2.5	7/0.67	2.01	0.72	1.35	19	7.98	0.05	452
10	4	7/0.85	2.55	0.72	1.35	21	4.95	0.05	635
10	6	7/1.04	3.12	0.9	1.44	25	3.3	0.05	931
11	1	7/0.43	1.29	0.72	1.35	16	19.5	0.05	268
11	1.5	7/0.52	1.56	0.72	1.35	17	13.3	0.05	345
11	2.5	7/0.67	2.01	0.72	1.35	19	7.98	0.05	480
11	4	7/0.85	2.55	0.72	1.35	21	4.95	0.05	677
11	6	7/1.04	3.12	0.9	1.44	25	3.3	0.05	996
12	1	7/0.43	1.29	0.72	1.35	17	19.5	0.05	288
12	1.5	7/0.52	1.56	0.72	1.35	18	13.3	0.05	369
12	2.5	7/0.67	2.01	0.72	1.35	20	7.98	0.05	517
12	4	7/0.85	2.55	0.72	1.35	22	4.95	0.05	732
12	6	7/1.04	3.12	0.9	1.53	26	3.3	0.05	1085

13	1	7/0.43	1.29	0.72	1.35	17	19.5	0.05	311
13	1.5	7/0.52	1.56	0.72	1.35	19	13.3	0.05	400
13	2.5	7/0.67	2.01	0.72	1.35	21	7.98	0.05	560
13	4	7/0.85	2.55	0.72	1.35	23	4.95	0.05	794
13	6	7/1.04	3.12	0.9	1.53	28	3.3	0.05	1178
14	1	7/0.43	1.29	0.72	1.35	17	19.5	0.05	324
14	1.5	7/0.52	1.56	0.72	1.35	19	13.3	0.05	418
14	2.5	7/0.67	2.01	0.72	1.35	21	7.98	0.05	588
14	4	7/0.85	2.55	0.72	1.35	23	4.95	0.05	836
14	6	7/1.04	3.12	0.9	1.53	28	3.3	0.05	1242
15	1	7/0.43	1.29	0.72	1.35	18	19.5	0.05	349
15	1.5	7/0.52	1.56	0.72	1.35	20	13.3	0.05	450
15	2.5	7/0.67	2.01	0.72	1.35	22	7.98	0.05	634
15	4	7/0.85	2.55	0.72	1.35	24	4.95	0.05	902
15	6	7/1.04	3.12	0.9	1.53	29	3.3	0.05	1339
16	1	7/0.43	1.29	0.72	1.35	18	19.5	0.05	361
16	1.5	7/0.52	1.56	0.72	1.35	20	13.3	0.05	469
16	2.5	7/0.67	2.01	0.72	1.35	22	7.98	0.05	662
16	4	7/0.85	2.55	0.72	1.44	24	4.95	0.05	953
16	6	7/1.04	3.12	0.9	1.62	30	3.3	0.05	1414
17	1	7/0.43	1.29	0.72	1.35	19	19.5	0.05	366
17	1.5	7/0.52	1.56	0.72	1.35	20	13.3	0.05	476
17	2.5	7/0.67	2.01	0.72	1.35	23	7.98	0.05	674
17	4	7/0.85	2.55	0.72	1.44	26	4.95	0.05	974
17	6	7/1.04	3.12	0.9	1.62	31	3.3	0.05	1444
18	1	7/0.43	1.29	0.72	1.35	19	19.5	0.05	382
18	1.5	7/0.52	1.56	0.72	1.35	20	13.3	0.05	497
18	2.5	7/0.67	2.01	0.72	1.35	23	7.98	0.05	706
18	4	7/0.85	2.55	0.72	1.44	26	4.95	0.05	1022
18	6	7/1.04	3.12	0.9	1.62	31	3.3	0.05	1517
19	1	7/0.43	1.29	0.72	1.35	19	19.5	0.05	397
19	1.5	7/0.52	1.56	0.72	1.35	20	13.3	0.05	519

19	2.5	7/0.67	2.01	0.72	1.35	23	7.98	0.05	739
19	4	7/0.85	2.55	0.72	1.44	26	4.95	0.05	1070
19	6	7/1.04	3.12	0.9	1.62	31	3.3	0.05	1590
20	1	7/0.43	1.29	0.72	1.35	20	19.5	0.05	418
20	1.5	7/0.52	1.56	0.72	1.35	21	13.3	0.05	546
20	2.5	7/0.67	2.01	0.72	1.35	24	7.98	0.05	778
20	4	7/0.85	2.55	0.72	1.44	27	4.95	0.05	1127
20	6	7/1.04	3.12	0.9	1.62	33	3.3	0.05	1686
21	1	7/0.43	1.29	0.72	1.35	20	19.5	0.05	434
21	1.5	7/0.52	1.56	0.72	1.35	21	13.3	0.05	568
21	2.5	7/0.67	2.01	0.72	1.35	24	7.98	0.05	810
21	4	7/0.85	2.55	0.72	1.44	27	4.95	0.05	1175
21	6	7/1.04	3.12	0.9	1.62	33	3.3	0.05	1759
22	1	7/0.43	1.29	0.72	1.35	21	19.5	0.05	455
22	1.5	7/0.52	1.56	0.72	1.35	22	13.3	0.05	595
22	2.5	7/0.67	2.01	0.72	1.35	25	7.98	0.05	849
22	4	7/0.85	2.55	0.72	1.44	28	4.95	0.05	1232
22	6	7/1.04	3.12	0.9	1.62	34	3.3	0.05	1844
23	1	7/0.43	1.29	0.72	1.35	21	19.5	0.05	470
23	1.5	7/0.52	1.56	0.72	1.35	22	13.3	0.05	617
23	2.5	7/0.67	2.01	0.72	1.35	25	7.98	0.05	881
23	4	7/0.85	2.55	0.72	1.44	28	4.95	0.05	1280
23	6	7/1.04	3.12	0.9	1.62	34	3.3	0.05	1917
24	1	7/0.43	1.29	0.72	1.35	22	19.5	0.05	493
24	1.5	7/0.52	1.56	0.72	1.35	23	13.3	0.05	646
24	2.5	7/0.67	2.01	0.72	1.44	26	7.98	0.05	932
24	4	7/0.85	2.55	0.72	1.62	30	4.95	0.05	1362
24	6	7/1.04	3.12	0.9	1.62	36	3.3	0.05	2005
25	1	7/0.43	1.29	0.72	1.35	22	19.5	0.05	508
25	1.5	7/0.52	1.56	0.72	1.35	23	13.3	0.05	667
25	2.5	7/0.67	2.01	0.72	1.44	26	7.98	0.05	964
25	4	7/0.85	2.55	0.72	1.62	30	4.95	0.05	1410

25	6	7/1.04	3.12	0.9	1.62	36	3.3	0.05	2078
26	1	7/0.43	1.29	0.72	1.35	22	19.5	0.05	524
26	1.5	7/0.52	1.56	0.72	1.35	23	13.3	0.05	689
26	2.5	7/0.67	2.01	0.72	1.44	26	7.98	0.05	996
26	4	7/0.85	2.55	0.72	1.62	30	4.95	0.05	1458
26	6	7/1.04	3.12	0.9	1.62	36	3.3	0.05	2151
27	1	7/0.43	1.29	0.72	1.35	22	19.5	0.05	542
27	1.5	7/0.52	1.56	0.72	1.35	24	13.3	0.05	713
27	2.5	7/0.67	2.01	0.72	1.53	27	7.98	0.05	1042
27	4	7/0.85	2.55	0.72	1.62	31	4.95	0.05	1511
27	6	7/1.04	3.12	0.9	1.62	37	3.3	0.05	2230
28	1	7/0.43	1.29	0.72	1.35	23	19.5	0.05	562
28	1.5	7/0.52	1.56	0.72	1.35	25	13.3	0.05	740
28	2.5	7/0.67	2.01	0.72	1.53	28	7.98	0.05	1081
28	4	7/0.85	2.55	0.72	1.62	32	4.95	0.05	1580
28	6	7/1.04	3.12	0.9	1.62	38	3.3	0.05	2312
29	1	7/0.43	1.29	0.72	1.35	23	19.5	0.05	578
29	1.5	7/0.52	1.56	0.72	1.35	25	13.3	0.05	761
29	2.5	7/0.67	2.01	0.72	1.53	28	7.98	0.05	1113
29	4	7/0.85	2.55	0.72	1.62	32	4.95	0.05	1628
29	6	7/1.04	3.12	0.9	1.62	38	3.3	0.05	2385
30	1	7/0.43	1.29	0.72	1.44	23	19.5	0.05	602
30	1.5	7/0.52	1.56	0.72	1.44	25	13.3	0.05	792
30	2.5	7/0.67	2.01	0.72	1.53	28	7.98	0.05	1146
30	4	7/0.85	2.55	0.72	1.62	32	4.95	0.05	1677
30	6	7/1.04	3.12	0.9	1.62	38	3.3	0.05	2458

Other dimensions and colours are possible on request.