



APPLICATION

Use in domestic premises, kitchens and offices, for ordinary duty applications and supplying appliances where cables are subject to low mechanical stresses (e.g. vacuum cleaners, cooking appliances, soldering irons, toasters, domestic portable tools, hand held inspection lamps) use outdoors for temporary periods of short duration.

CHARACTERISTICS

Voltage Rating U/U₀

300/500V

Temperature Rating

Operating: -5°C to +110°C

Maximum temperature of short circuit: +250°C

Minimum Bending Radius

Fixed: 3 x overall diameter

Mobile: 4 x overall diameter

CONSTRUCTION

Conductor

Class 5 flexible tinned copper conductor

Insulation

EVA Rubber (Ethylene Vinyl Acetate) EI3

Sheath

Rubber EM4

Core Identification

2 core: Blue Brown

3 core: Green/Yellow Blue Brown

4 core: Green/Yellow Brown Black Grey

5 core: Green/Yellow Blue Brown Black Grey

Sheath Colour

Black

STANDARDS

EN 50525-2-21

Cable Parameter

AWG	No. of Cores x Nominal Cross Sectional Area	Nominal Thickness of Insulation	Nominal Thickness of sheath	Nominal Overall Diameter	Nominal Weight
	# x mm ²	mm	mm	mm	kg/Km



18(24/32)	2x0.75	0.6	0.8	6.3	53
17(32/32)	2x1	0.6	0.9	6.8	64
16(30/30)	2x1.5	0.8	1	8.3	95
14(30/50)	2x2.5	0.9	1.1	9.8	140
18(24/32)	3x0.75	0.6	0.9	6.8	65
17(32/32)	3x1	0.6	0.9	7.2	77
16(30/30)	3x1.5	0.8	1	8.8	115
14(30/50)	3x2.5	0.9	1.1	10.4	170
12(56/28)	3 x 4	1	1.2	12.2	240
10(84/28)	3 x 6	1	1.4	13.6	320
18(24/32)	4x0.75	0.6	0.9	7.4	80
17(32/32)	4x1	0.6	0.9	7.8	95
16(30/30)	4x1.5	0.8	1.1	9.8	145
14(30/50)	4x2.5	0.9	1.2	11.5	210
12(56/28)	4 x 4	1	1.3	13.5	300
10(84/28)	4 x 6	1	1.5	15.4	405
18(24/32)	5x0.75	0.6	1	8.3	100
17(32/32)	5x1	0.6	1	8.7	115
16(30/30)	5x1.5	0.8	1.1	10.7	170
14(30/50)	5x2.5	0.9	1.3	12.8	255