



Application

These cables are used with thermocouples for temperature measurements.

Conductor

Solid. Material is according to thermocouple type.

Insulation

FEP

Outer sheath

FEP

Construction

Flat

Color code

According to IEC 60584-3

Construction Parameters

K Type

AWG(MM)	INSULATION MATERIAL	SHEATH MATERIAL	MAX. TEMP. (°C)	NOMINAL O.D. (MM)	WEIGHT (KG/KM)
30(0.25)	FEP	FEP	200	1.2 x 1.8	4.5
28(0.32)	FEP	FEP	200	1.2 x 2.0	5.5
26(0.41)	FEP	FEP	200	1.3 x 2.1	6.5
24 (0.51)	FEP	FEP	200	1.4 x 2.4	10.0
20 (0.81)	FEP	FEP	200	1.7 x 3.0	16.7

E Type

AWG(MM)	INSULATION MATERIAL	SHEATH MATERIAL	MAX. TEMP. (°C)	NOMINAL O.D. (MM)	WEIGHT (KG/KM)
30(0.25)	FEP	FEP	200	1.2 x 1.8	4.5
28(0.32)	FEP	FEP	200	1.2 x 2.0	5.5
26(0.41)	FEP	FEP	200	1.3 x 2.1	6.5
24 (0.51)	FEP	FEP	200	1.4 x 2.4	10.0
20 (0.81)	FEP	FEP	200	1.7 x 3.0	16.7

J Type

AWG(MM)	INSULATION MATERIAL	SHEATH MATERIAL	MAX. TEMP. (°C)	NOMINAL O.D. (MM)	WEIGHT (KG/KM)
30(0.25)	FEP	FEP	200	1.2 x 1.8	4.5

28(0.32)	FEP	FEP	200	1.2 x 2.0	5.5
26(0.41)	FEP	FEP	200	1.3 x 2.1	6.5
24 (0.51)	FEP	FEP	200	1.4 x 2.4	10.0
20 (0.81)	FEP	FEP	200	1.7 x 3.0	16.7