



Application

These cables are used with thermocouples for temperature measurements.

Conductor

Solid or stranded. Material is according to thermocouple type.

Insulation

TFE Tape Polymer

Outer sheath

Fused TFE Tape Polymer

Construction

Flat

Color code

According to IEC 60584-3

Construction Parameters

K Type

| AWG(MM) | INSULATION MATERIAL | SHEATH MATERIAL | MAX. TEMP. (°C) | NOMINAL O.D. (MM) | WEIGHT (KG/KM) |
|-------------|---------------------|------------------------|-----------------|-------------------|----------------|
| 24 (0.51) | TFE Tape Polymer | Fused TFE Tape Polymer | 260 | 1.3 x 1.9 | 10.0 |
| 24 (7/0.2) | TFE Tape Polymer | Fused TFE Tape Polymer | 260 | 1.3 x 2.2 | 10.3 |
| 20 (0.81) | TFE Tape Polymer | Fused TFE Tape Polymer | 260 | 1.5 x 2.5 | 16.7 |
| 20 (7/0.32) | TFE Tape Polymer | Fused TFE Tape Polymer | 260 | 1.5 x 2.7 | 17.1 |

E Type

| AWG(MM) | INSULATION MATERIAL | SHEATH MATERIAL | MAX. TEMP. (°C) | NOMINAL O.D. (MM) | WEIGHT (KG/KM) |
|-------------|---------------------|------------------------|-----------------|-------------------|----------------|
| 24 (0.51) | TFE Tape Polymer | Fused TFE Tape Polymer | 260 | 1.3 x 1.9 | 10.0 |
| 24 (7/0.2) | TFE Tape Polymer | Fused TFE Tape Polymer | 260 | 1.3 x 2.2 | 10.3 |
| 20 (0.81) | TFE Tape Polymer | Fused TFE Tape Polymer | 260 | 1.5 x 2.5 | 16.7 |
| 20 (7/0.32) | TFE Tape Polymer | Fused TFE Tape Polymer | 260 | 1.5 x 2.7 | 17.1 |