



Applications:

XHHWXLPO type TC Control Cable is for use in industrial power or control circuits where small diameter, flame retardant cables are desired. Primary installations include cable trays, raceways, and outdoor locations where supported by a messenger wire. Type TC Control Cable is also listed for direct burial and for use in Class 1, Division 2 hazardous locations and Class 1 control circuits. Constructions with 3 or more conductors are listed for exposed runs (TC-ER) per NEC 336.10. Conductors may be used in wet or dry locations at temperatures not to exceed 90°C.

Construction:

Conductor:

Stranded bare annealed copper

Insulation:

Flame-retardant and moisture resistant Cross-Linked Polyethylene (XLPE)

Jacket: Low smoke halogen free polyethylene jacket

Color: upon request, black is preferable

Compliances:

UL 1277 - Electrical Power and Control Tray Cables.

UL 1581 - Electrical Wires, Cables and Flexible Cords

ICEA S-58-679 Method 1

UL 1685 - UL Flame Exposure Test (70,000 Btu/hr).

ICEA T-29-520 - Vertical Cable Tray Flame Test (210,000 Btu/hr).

IEEE 1202 - Flame Testing of Cables for Use in Cable Tray in Industrial and Commercial Occupancies (70,000 Btu/hr)

ICEA S-95-658 (NEMA WC 70) RoHS

Parameters:

No. of Cores	Nominal jacket Thickness Inch/ mm	Nominal Overall Diameter Inch/mm	Cable Weight Lbs/ kft kg/ km	
AWG 14 (7 strands)				
2	0.045	0.349	8.86	63 94
3	0.045	0.370	9.40	87 129
4	0.045	0.403	10.24	106 157
5	0.045	0.440	11.18	125 186
6	0.045	0.479	12.17	146 218
7	0.045	0.479	12.17	164 245
8	0.060	0.549	13.94	201 299
9	0.060	0.588	14.94	223 332
10	0.060	0.638	16.21	247 367
12	0.060	0.659	16.74	285 424
15	0.060	0.730	18.54	347 517
19	0.060	0.768	19.51	424 630
20	0.060	0.808	20.52	446 664
25	0.080	0.938	23.83	582 866
30	0.080	0.991	25.17	680 1012
37	0.080	1.067	27.10	818 1217
AWG 12 (7 strands)				

2	0.045	1.14	0.384	9.75	85	127
3	0.045	1.14	0.408	10.36	115	172
4	0.045	1.14	0.445	11.30	147	219
5	0.045	1.14	0.487	12.37	171	255
6	0.060	1.52	0.562	14.27	217	323
7	0.060	1.52	0.562	14.27	244	363
8	0.060	1.52	0.607	15.42	275	410
9	0.060	1.52	0.651	16.54	307	457
10	0.060	1.52	0.709	18.01	340	506
12	0.060	1.52	0.732	18.59	396	589
15	0.060	1.52	0.813	20.65	484	721
19	0.080	2.03	0.896	22.76	628	934
20	0.080	2.03	0.942	23.93	661	984
25	0.080	2.03	1.043	26.49	811	1207
30	0.080	2.03	1.104	28.04	953	1418
37	0.080	2.03	1.190	30.23	1152	1714
AWG 10 (7 strands)						
2	0.045	1.14	0.431	10.95	116	172
3	0.045	1.14	0.459	11.66	161	239
4	0.045	1.14	0.502	12.75	205	306
5	0.060	1.52	0.581	14.76	260	387
6	0.060	1.52	0.632	16.05	306	455
7	0.060	1.52	0.632	16.05	346	514
8	0.060	1.52	0.685	17.40	392	583
9	0.060	1.52	0.736	18.69	437	651
10	0.060	1.52	0.803	20.40	485	721
12	0.080	2.03	0.870	22.10	599	892
15	0.080	2.03	0.964	24.49	733	1091
19	0.080	2.03	1.014	25.76	901	1340
20	0.080	2.03	1.066	27.08	949	1412
25	0.080	2.03	1.184	30.07	1168	1739
30	0.080	2.03	1.254	31.85	1379	2052
37	0.080	2.03	1.355	34.42	1674	2491